

GENERATORS 1500 R.P.M. DIESEL (SOUNDPROOF)

Engine plus alternator kit assembled directly by a flexible disc and mounted on a bench through silent blocks to take completely the vibrations.



	Engine	Model	R.P.M.	Rated output (Kva)	Emergency output (Kva)	Fuel	Power (kWm)	Consumption at 75% load (l/h)	Fuel tank capacity (l)	Sound level (dB at 7m)	Option for regular wheel kit	Option for non regular wheel kit	Automatic board kit	Weight (kg)
YANMAR engine, soundproof, water-cooled														
WYW 15 I	Yanmar	3TNE88	1500	13,5	15	Diesel	12,5	2,3	40	69	NO	YES	YES	477
WYW 20 I	Yanmar	4TNE88	1500	18	20	Diesel	16,4	2,9	60	66	NO	YES	YES	617
DEUTZ engine, soundproof, oil-cooled														
WDOIL 25 I	Deutz	F3M 1011 F	1500	20	21	Diesel	18	3,6	100	69	NO	YES	YES	880
WDOIL 30 I	Deutz	F4M 1011 F	1500	28	29	Diesel	24,9	4,9	150	69	NO	YES	YES	1035
WDOIL 45 I	Deutz	BF4M 1011 F	1500	38	41	Diesel	35,3	7,2	150	69	NO	YES	YES	1100

YANMAR ENGINE, SOUNDPROOF, WATER-COOLED. Diesel engine water-cooled, four strokes, direct injection at 1500 rpm. Low oil and fuel consumption. Electronic regulation (AVR) four poles and class H isolation.

DEUTZ ENGINE, SOUNDPROOF, OIL-COOLED. Diesel engine of the 1011 Series, oil-cooled, four strokes, direct injection at 1500 rpm. Low oil and fuel consumption. Electronic regulation (AVR), four poles and class H isolation.



GENERATORS 1500 R.P.M. DIESEL (SOUNDPROOF)

DEUTZ ENGINE, SOUNDPROOF, WATER COOLED. Engine plus alternator kit assembled directly by a flexible disc and mounted on a bench through silent blocks to take completely the vibrations. Diesel engine 1012, 1013 and 1015 Series, oil-cooled, four strokes, direct injection at 1500 rpm. Low oil and fuel consumption. Electronic regulation (AVR), four poles and class H isolation.



	Engine	Model	R.P.M.	Rated output (Kva)	Emergency output (Kva)	Fuel	Power (kWm)	Consumption at 75% load (l/h)	Fuel tank capacity (l)	Sound level (dB at 7m)	Option for regular wheel kit	Option for non regular wheel kit	Automatic board kit	Weight (kg)
WDW 65 I	Deutz	BF4M 1012 E	1500	60	63	Diesel	53	13,3	150	75	YES	YES	YES	1425
WDW 80 I	Deutz	BF4M 1012 EC	1500	75	78	Diesel	66	16,1	150	75	YES	YES	YES	1470
WDW 115 I	Deutz	BF4M 1013 EC	1500	108	114	Diesel	97	23,8	165	75	YES	YES	YES	1800
WDW 145 I	Deutz	BF6M 1013 E	1500	139	144	Diesel	122	30,2	220	75	YES	YES	YES	2120
WDW 175 I	Deutz	BF6M 1013 EC	1500	165	173	Diesel	146	34,4	220	75	YES	YES	YES	2300
WDW 255 I	Deutz	BF6M 1015	1500	230	254	Diesel	210	53,2	680	75	NO	NO	YES	3600
WDW 350 I	Deutz	BF6M 1015 C	1500	315	346	Diesel	285	66,8	680	75	NO	NO	YES	3800
WDW 420 I	Deutz	BF6M 1015 CP	1500	378	416	Diesel	338	79,3	560	75	NO	NO	YES	4000
WDW 470 I	Deutz	BF8M 1015 C	1500	425	467	Diesel	380	89,1	850	75	NO	NO	YES	5400
WDW 555 I	Deutz	BF8M 1015 CP	1500	505	555	Diesel	448	106,1	850	75	NO	NO	YES	5500

GENERATORS 1500 R.P.M. DIESEL (SOUNDPROOF)

VOLVO ENGINE, SOUNDPROOF, WATER-COOLED. Engine plus alternator kit assembled directly by a flexible disc and mounted on a bench through silent blocks to take completely the vibrations. Diesel engine of the series oil-cooled, four strokes, direct injection at 1500 rpm with 6 cylinders and turbocompressor. Low oil and fuel consumption. Electronic regulation (AVR), four poles and class H isolation. Including radiator and ventilator to cool the engine.



WVV 205 I	3500 x 1300 x 1950
WVV 230 I	3500 x 1300 x 1950
WVV 275 I	3500 x 1300 x 1950
WVV 330 I	4000 x 1600 x 2100
WVV 360 I	4000 x 1600 x 2100
WVV 410 I	4000 x 1600 x 2100
WVV 450 I	4000 x 1600 x 2100
WVV 505 I	5000 x 1800 x 2100
WVV 560 I	5000 x 1800 x 2100
PACKAGING DIMENSIONS (mm.)	

	Engine	Model	R.P.M.	Rated output (Kva)	Emergency output (Kva)	Fuel	Power (kWm)	Consumption at 75% load (lh)	Fuel tank capacity (l)	Sound level (dBA 7m)	Option regular wheel	Option of wheel trolley with fix axle	Option automatic board	Weight (Kg)
WVV 205 I	Volvo	TWD 710 G	1500	185	204	Diesel	163	26,5	350	75	YES	YES	YES	2950
WVV 230 I	Volvo	TWD 740 GE	1500	205	226	Diesel	178	32,6	350	75	YES	YES	YES	3365
WVV 275 I	Volvo	TAD 740 GE	1500	250	275	Diesel	217	38,4	350	75	YES	YES	YES	3490
WVV 330 I	Volvo	TAD 1032 GE	1500	301	329	Diesel	266	49	600	75	NO	NO	YES	3950
WVV 360 I	Volvo	TAD 1240 GE	1500	327	356	Diesel	283	49,8	600	75	NO	NO	YES	4000
WVV 410 I	Volvo	TAD 1241 GE	1500	371	409	Diesel	323	56,2	600	75	NO	NO	YES	4400
WVV 450 I	Volvo	TAD 1242 GE	1500	409	450	Diesel	353	62,9	600	75	NO	NO	YES	4500
WVV 505 I	Volvo	TAD 1630 GE	1500	459	505	Diesel	395	71,2	885	75	NO	NO	YES	5250
WVV 560 I	Volvo	TAD 1631 GE	1500	505	556	Diesel	430	78,7	885	75	NO	NO	YES	5600

